



2.5mm² TU接线端子
TU Terminal Block

4mm² TU接线端子
TU Terminal Block

6mm² TU接线端子
TU Terminal Block

10mm² TU接线端子
TU Terminal Block

16mm² TU接线端子
Ground Terminal Block

技术参数Technical Parameter			
尺寸Size	厚度Thickness	宽度Width	高度Height
注: 安装NS35/7.5导轨后的高度 Note: Height With DIN Rail NS 35/7.5	[mm]	5.2	46.2
额定参数Rated Parameters			
额定电压Rated Voltage	IEC	UL	
	1000	600	
额定电流Rated Current	[A]	24	20
接线容量Wire Range			
	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	[mm ²]	0.2-4	0.25-2.5
	[AWG]	26-12	26-12
螺钉类型Screw Type	[*]	M2.5	
扭矩Torque	[N.m]	0.4	
其余参数Other Parameters			
绝缘材料/阻燃等级, 符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		V0	
剥线长度Strip length	[mm]	8-9	
订货信息Order Information			
产品Product	颜色Colour	订货号Order NO.	
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5	灰Gray	TU2.5-2-GY	
	橙Orange	TU2.5-2-OG	
	蓝Blue	TU2.5-2-BU	
配套附件Accessory			
盖板Cover Plate	颜色Colour	订货号Order NO.	
盖板Cover Plate	灰Gray	TU2.5-2-GY-EA	
	橙Orange	TU2.5-2-OG-EA	
跨接件Jumper			
极数Poles No.	订货号Order NO.		
2	TJA5.2-2		
3	TJA5.2-3		
4	TJA5.2-4		
5	TJA5.2-5		
6	TJA5.2-6		
7	TJA5.2-7		
8	TJA5.2-8		
9	TJA5.2-9		
10	TJA5.2-10		
正面标记(小)Front Marker(Small)	订货号Order NO.		
可提供印字服务Printing Service	TMB5.2-120		
正面标记(大)Front Marker(Big)	订货号Order NO.		
可提供印字服务Printing Service	305801		

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
6.2	47.3	46.2
额定参数Rated Parameters		
IEC	UL	
1000	600	
32	30	
接线容量Wire Range		
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-6	0.2-4	0.2-4
26-10	26-10	26-10
其余参数Other Parameters		
	V0	
	8-9	
订货信息Order Information		
订货号Order NO.		
TU4-2-GY		
TU4-2-OG		
TU4-2-BU		
配套附件Accessory		
订货号Order NO.		
TU2.5-2-GY-EA		
TU2.5-2-OG-EA		
跨接件Jumper		
订货号Order NO.		
TJA6.2-2		
TJA6.2-3		
TJA6.2-4		
TJA6.2-5		
TJA6.2-6		
TJA6.2-7		
TJA6.2-8		
TJA6.2-9		
TJA6.2-10		
订货号Order NO.		
TMB6.2-100		
订货号Order NO.		
306801		

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
8.2	47.3	46.2
额定参数Rated Parameters		
IEC	UL	
1000	600	
41	50	
接线容量Wire Range		
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-10	0.2-6	0.25-6
24-8	24-8	24-8
其余参数Other Parameters		
	M4	
	1.2	
	V0	
	9-10	
订货信息Order Information		
订货号Order NO.		
TU6-2-GY		
TU6-2-OG		
TU6-2-BU		
配套附件Accessory		
订货号Order NO.		
TU2.5-2-GY-EA		
TU2.5-2-OG-EA		
跨接件Jumper		
订货号Order NO.		
TJA8.2-2		
TJA8.2-3		
TJA8.2-4		
TJA8.2-5		
TJA8.2-6		
TJA8.2-7		
TJA8.2-8		
TJA8.2-9		
TJA8.2-10		
订货号Order NO.		
TMB8.2-50		
订货号Order NO.		
308801		

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
10.2	47.3	46.2
额定参数Rated Parameters		
IEC	UL	
1000	600	
57	65	
接线容量Wire Range		
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.5-16	0.5-10	0.5-10
20-6	20-6	20-6
其余参数Other Parameters		
	M4	
	1.2	
	V0	
	10-11	
订货信息Order Information		
订货号Order NO.		
TU10-2-GY		
TU10-2-OG		
TU10-2-BU		
配套附件Accessory		
订货号Order NO.		
TU2.5-2-GY-EA		
TU2.5-2-OG-EA		
跨接件Jumper		
订货号Order NO.		
TJA10.2-2		
*		
*		
*		
*		
*		
*		
*		
订货号Order NO.		
TMB10.2-10		
订货号Order NO.		
310801		

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
12.2	52.8	54.35
额定参数Rated Parameters		
IEC	UL	
1000	600	
76	85	
接线容量Wire Range		
刚性Solid	柔性Fine Stranded	带冷压头Furrule
1.5-25	1.5-16	1.5-16
16-4	16-4	16-4
其余参数Other Parameters		
	M5	
	2.0	
	V0	
	13-14	
订货信息Order Information		
订货号Order NO.		
TU16-2-GY		
TU16-2-OG		
TU16-2-BU		
配套附件Accessory		
订货号Order NO.		
TU16-2-GY-EA		
TU16-2-OG-EA		
跨接件Jumper		
订货号Order NO.		
TJA12.2-2		
*		
*		
*		
*		
*		
订货号Order NO.		
TMB10.2-10		
订货号Order NO.		
310801		